



## ASP165 (SINGLE-PHASE) - ASP165T (THREE-PHASE) CHIP AND DUST COLLECTOR • 165 L




- High air flow, high collecting capacity.
- 3 input ports Ø 100 mm to connect woodworking machines, fan housing can be turned over to make dust inlet upward, depending on the machines and the layout of the workshop.
- Easy and quick assembling.
- Powerful 1500 W induction motor, tough and silent.
- Mechanically welded fan housing and filtration housing.
- Steel base mounted on 4 casters.



Felt filter bag



Steel propeller



Strap + bag holding clip

WARRANTY	2
Voltage/Frequency	230 V / 50 Hz (ASP165) 400 V / 50 Hz (ASP165T)
Motor power	1500 W - S1
Rotation speed	2800 rpm
Propeller diameter	Ø 300 mm
Fan inlet diameter	Ø 150 mm
Number of connections	3 Ø100 mm
Hose length	2 m
Air flow	2900 m <sup>3</sup> /h
Bag diameter	500 mm
Collection bag height	1250 mm
Collection capacity	1x165 l
Filter bag height	1100 mm
Bag filter	5 µ
Sound pressure LpA	83.4 dB(A) no load
Sound power LwA	98.17 dB(A) no load
Net weight	45 kg
Gross weight	48 kg
Dimensions	985 x 560 x 2220 mm
Packing dimensions	1050 x 610 x 520 mm
Spare parts reference - Mono	091300 (+ N°/ exploded view)
- Tri	091400 (+ N°/ exploded view)
Gencod	3661589102560
- Tri	3661589102577

### ACCESSORIES AND OPTIONS

- The machine comes with 1 felt filter bag, 1 plastic collection bag, 2 straps, 2 connector covers, 2 m hose, 2 hose clamps, 4 wheels and instructions manual.

	REF
Plastic collection bag ø 500 x 1250 mm	090101
Felt filter bag ø 500 x 1100 mm	091303
Strap for bag	090104
Hose clamp · ø 100	090006
PVC hose (unit = 1 meter) · ø 100 mm	090005

