

## ENT032 (SINGLE-PHASE) AUTOMATIC POWER FEEDER




185W



30 Kg



- The power feeder allows the workpiece to move evenly, while providing maximum safety.
- 4 feeding speeds forwards and backwards by changing the pinions position.
- Interchangeable pinions in sintered carbide, carbonitrided and treated.
- Very resistant and protective electrostatic powder paint.
- Possibility to work at 90 ° for feeding the workpiece on the edge against the fence (using of fence with sliding segments is recommended).
- Handwheel with worm screw for horizontal and vertical adjustments, round steel rods Ø 40 mm.



Chain drive



Arm extended by 610 mm



3 rollers ø 80

WARRANTY	2
Motor power (230 V - 50 HZ)	185 W - S3
Dimensions	1040 x 350 x 600 mm
Direction of rotation	Forward and backward
Drive speed	4 - 8 - 9 - 18 m/min
Number of rollers	3
Roller diameter	80 mm
Roller width	28 mm
Thickness of rubber rollers	14 mm
Roller suspension stroke	15 mm
Arm stroke	425 mm
Bracket stroke	150 mm
Max. height of workpiece	150 mm
Net weight	30 kg
Spare parts reference	250200 (+ N°/ exploded view)
Gencod	3700501704984
Packing	700 x 580 x 280 mm
Gross weight	37 Kg

### ACCESSORIES AND OPTIONS

- Comes with 3 rubber rollers, ø 80 mm, 610 mm extended arm and instructions manual.



	REF
Rubber Roller Ø 80 mm	250200.005