

LODRA260 (SINGLE-PHASE)

THICKNESSER-PLANER • 260 MM



- Transportable machine, ideal for construction sites and workshop.
- Fixing holes on the base allowing the machine to be fixed on the 4-leg stand supplied as standard equipment or a workbench, with 4 rubber foot pads to limit vibrations.
- Integrated suction system with chip & dust collector bag.
- Storage box for accessories.
- Die-cast aluminum planing tables fully rectified, with anti-noise lips.
- Thicknessing table in galvanized steel.
- Planer's fence in aluminum extrusion. tiltable up to 45°



Profiled aluminium guide tilting at 45°

WARRANTY	2
Motor power (230 V - 50 Hz)	1500 W - (carbon brush) - S1
Dimensions	960 x 515 x 1100 mm
Cutterblock rotation speed	9000 rpm
Cutterblock diameter	50 mm
Number of blades	2
Blade dimensions	260 x 16,5 x 1,5 mm (1 cut)
Drive roller diameter	25 mm
Suction outlet	100 mm
Planer	
Planing width	260 mm
Dimensions of tables	920 x 265 mm
Guide dimensions	635 x 125 mm
Guide tilt	from 90° to 135°
Cutting depth	from 0 to 2 mm
Working height	970 mm
Thicknesser	
Thicknessing width	255 mm
Thicknessing height	from 5 to 120 mm
Max. thicknessing length	1000 mm
Cutting depth	up to 3 mm
Feed speed	6 m/min
Table dimensions	270 x 303 mm
Net weight	33,50 Kg
Spare parts reference	210600 (+ N°/ exploded view)
Gencod	3700501707817
Packing - Machine	1020 x 510 x 440 mm
Gross weight	39 Kg

ACCESSORIES AND OPTIONS

- The machine comes with a 4-leg-stand, a tilting guide, 2 x HSS18% steel blades, 1 blade adjustment gauge, pushers, spanners and instructions manual.



REF

260 16,5 1,5 HSS18% steel blade

210601