

LOPON150 (SINGLE-PHASE)

DISC & BELT SANDER • 150 MM



- Cast iron body combining strength and stability, with fixing holes on the base.
- Powerful induction motor 370 W, tough and silent.
- Sawdust collector on the belt, Ø 67 mm suction outlet in common with the disc which facilitates the connection with a vacuum.
- Limiting plate at the end of the sanding belt table. Properly sized, it also ducts sawdust towards the collector.
- Quick release belt tension lever located at the front of the machine, the belt can be easily taken out without disassembling anything.
- Belt tracking knob also located at the front.
- Cast aluminum table tiltable up to 45 ° downwards.
- ± 60 ° adjustable miter gauge for sanding bevelled parts.
- Sanding belt table can be raised at 90 °, with the possibility of fixing the sanding disc table for better comfort.



Cast aluminium table
tilting at 45°

WARRANTY	2
Motor power (230 V - 50 Hz)	370 W - S1
Dimensions	480 x 350 x 325 mm
Table dimensions	215 x 146 mm
Tilt	downward 45°
Angle guide	- 60° to + 60°
Suction outlet	ø 67 mm
Sanding disc	
Diameter	150 mm
Attachment	adhesive
Rotation speed	2850 rpm
Sanding belt	
Basic dimensions	914 x 100 mm
Speed	435 m/min
Tilt	0° and 90°
Length of the support table	310 mm
Net weight	16 kg
Spare parts reference	190000 (+ N°/ exploded view)
Gencod	3700501700269
Packing	560 x 315 x 350 mm
Gross weight	18 Kg

ACCESSORIES AND OPTIONS

- The machine comes with the mitre guide, 1 disc and 1 belt-80 grit, spanners and instructions manual.

