

**LORAB330  
 THICKNESSER • 330 MM**


- Very easy to use transportable machine, ideal for construction sites and workshop.
- Thicknessing table in galvanized steel, with infeed and outfeed extension tables.
- Integrated carrying handles.
- Reversible dust exhaust port with adaptors.



Galvanized steel thicknesser table



Depth gauge

<b>WARRANTY</b>	2
<b>Voltage/Frequency</b>	230 V / 50 Hz
<b>(Brush) motor power</b>	1500 W - S1
<b>Rotation speed</b>	8500 rpm
<b>Cutterblock diameter</b>	48 mm
<b>Number of blades</b>	2
<b>Blade dimensions</b>	330 x 12 x 1.5 mm 2 reversible cuts
<b>Suction outlet</b>	Ø 53 mm with adapters
<b>Thicknessing width</b>	330 mm
<b>Thicknessing height</b>	152 mm
<b>Table dimensions</b>	330 x 235 mm
<b>Cutting depth</b>	0.5 to 3.0 mm
<b>Feed speed</b>	6 m/min
<b>Sound pressure LpA</b>	83.8 dB(A) no load
<b>Sound power LwA</b>	96.8 dB(A) no load
<b>Net weight</b>	30.7 kg
<b>Gross weight</b>	33.1 kg
<b>Dimensions</b>	630 x 560 x 550 mm
<b>Packing dimensions</b>	620 x 410 x 475 mm
<b>Spare parts reference</b>	210800 (+N°/ exploded view)
<b>Gencod</b>	3661589102546

**ACCESSORIES AND OPTIONS**

- The machine comes with adapters ø 65 & 100 mm, 2 steel blades, service spanners and instructions manual.



				<b>REF</b>
330	12	1,5	HSS 18% steel - 2 reversible cuts (pair)	210801