



LOSRU250 (SINGLE-PHASE) BANDSAW • 250 MM



- Mechanically welded frame, rigid and strong.
- Fixing holes on the base allowing the machine to be fixed on a stand or a workbench.
- Ø 60 mm suction outlet at the rear of the machine.
- Induction motor, tough and silent.
- 45 ° tilting cast aluminum sawing table, graduations on each side of the blade, rip fence can be positioned on the right or left.
- ± 60 ° adjustable miter gauge, positionable to the right of the table.
- Upper and lower blade guides with 3 bearings.
- Adjustment of the blade tension with a knob.
- 2 cast aluminum wheels well balanced and covered with a rubber tyre.
- Cleaning brush on the drivewheel, allowing the blade to have a good grip.
- Safety switch on each door.



Balanced cast aluminium flywheels and safety contactors

WARRANTY	2
Motor power (230 V - 50 Hz)	350 W - S1
Dimensions	480 x 400 x 815 mm
Cutting width	245 mm
Cutting height	80 mm
Blade length	1710 mm
Blade width	6 to 13 mm
Table dimensions	300 x 300 mm
Table tilt	0 to 45°
Working height	375 mm
Flywheel diameter	250 mm
Cutting speed	700 m/min
Suction outlet	ø 60 mm
Net weight	25 Kg
Spare parts reference	110000 (+ N°/ exploded view)
Gencod	3700501700146
Packing	800 x 330 x 420 mm
Gross weight	29 Kg

ACCESSORIES AND OPTIONS

- The machine comes with a cast aluminium table, rip fence, mitre gauge, 1 x 8 mm blade, spanners and instructions manual.



REF

4-leg stand

110001

