


**LOSST315 (SINGLE-PHASE)**
**TRANSPORTABLE TABLE SAW WITH SLIDING CARRIAGE • 315 MM**


- Steel chipcase mounted on folding legs foldable without tools for easy assembly, storage or transportation.
- Wheel kit and 2 retractable handles for moving the machine easily.
- Powerful 2200 W induction motor, tough and silent.
- Ø 100 mm main dust outlet on the motor chipcase.
- Suction outlet Ø 30 mm on the blade guard, connected to the main dust outlet by a flexible hose (supplied).
- Cleaning hatch located under the chipcase to remove sawdust and wooden scraps.
- Galvanized steel sawing table.
- Galvanized steel rear extension table 550 x 800 mm, fitted with 2 supports.
- Blade height adjustable by a crank, and tiltable up to 45 ° to the right by a thumbwheel.
- Rip fence with cam locking handle and graduation.
- Sliding table for cross cutting mounted on guiding rail with 3 rollers.
- ± 45 ° adjustable miter gauge mounted on the sliding table, equipped with a length stop for repetitive cuts.



Tilting table at 45°



Foldable legs

<b>WARRANTY</b>	2
Motor power (230 V - 50 Hz)	2200 W - S6/20% - 5 min
Dimensions	915 x 1999 x 900 mm
Blade/rotation speed	2800 rpm
Blade diameter	315 mm
Blade bore	30 mm
Blade tilt	0° to 45° on the right
Working height	855 mm
Max. cutting height	83 mm
Cutting height at 45°	58 mm
Suction outlet	ø 100 mm
Table dimensions	550 x 800 mm
Dimensions of extension	550 x 800 mm
Guide dimensions	580 x 60 mm
Net weight	54 Kg
Spare parts reference	070100 (+ N°/ exploded view)
Gencod	3700501700078
<b>Packing</b>	
- Machine	940 x 650 x 470 mm
- Carriage	1280 x 240 x 140 mm
Gross weight	65 Kg

**ACCESSORIES AND OPTIONS**

- The machine comes with a rip fence, mitre gauge, 1 x 24 teeth TCT saw blade, sliding carriage, rear table extension, transportation kit, spanners and instructions manual.



OPTION

**REF**

Right extension table 070101

**REF**

Right extension table ruler 070102

CONSUMABLES

**SOLID WOOD**

222.315.3024 P. 84

328.315.3048 P. 86

**DERIVED FROM WOOD**

336.315.3072 P. 95

**MULTI-MATERIAL**

223.315.3020 P. 103

224.315.3048 P. 104