

CLASSIC



HM

EN847-1

LSC.00224

HOJA DE SIERRA DE OBRA MULTIMATERIALES

- Utilización para madera incluso con clavos y grapas, restos de hormigón.
- Adecuado igualmente para plásticos, plexiglás, perfiles de aluminio (no corta los metales).



MADERA, MADERA DE ENCOFRADO, MADERA TACHONADA

Ø		$\frac{\Phi}{\delta}$		REF		€
150	20	2,8/1,6	24	224.150.2024	3510782241005	60,56
160	20	2,8/1,6	24	224.160.2024	3510782241012	63,06
180	30	2,8/1,8	30	224.180.3030	3510782241036	72,08
190	30	2,8/1,8	30	224.190.3030	3510782241043	74,50
210	30	2,8/1,8	32	224.210.3034	3510782241067	82,32
230	30	2,8/1,8	34	224.230.3034	3510782241074	88,76
250	30	3,0/2,0	42	224.250.3042	3510782241104	109,36
300	30	3,2/2,2	48	224.300.3048	3510782241111	123,54
315	30	3,2/2,2	48	224.315.3048	3510782241128	135,08
350	30	3,2/2,2	54	224.350.3054	3510782241135	142,76
400	30	3,5/2,5	64	224.400.3060	3510782241142	159,44
450	30	3,5/2,5	66	224.450.3066	3510782241159	205,76
500	30	4,0/2,8	72	224.500.3072	3510782241166	261,04
600	30	4,2/2,9	78	224.600.3078	3510782241173	302,26