

METAL

TALADRADO


CLASSIC



PER.00804

BROCA METAL HSS CON 5 % DE COBALTO

- Uso intenso.
- Alta resistencia al calentamiento.
- Broca tallada de acero rápido M35 con cobalto (5 %).
- Afilado punta en cruz antideslizante.
- Ángulo de punta a 135° autocentrador.



ACERO INOXIDABLE, ACERO, FUNDICIÓN

| Ø | LU | LU | REF | REF | € | |
|-----|-----|-----|-----|-------------------|---------------|-------|
| 2 | 49 | 24 | 1 | 804.020.01 | 3661589011893 | 2,32 |
| 2 | 49 | 24 | 10 | 804.020.10 | 3661589054562 | 17,20 |
| 2,5 | 57 | 30 | 1 | 804.025.01 | 3661589011909 | 2,38 |
| 2,5 | 57 | 30 | 10 | 804.025.10 | 3661589054579 | 17,72 |
| 3 | 61 | 33 | 1 | 804.030.01 | 3661589011916 | 2,78 |
| 3 | 61 | 33 | 10 | 804.030.10 | 3661589054586 | 20,56 |
| 3,5 | 70 | 39 | 1 | 804.035.01 | 3661589011923 | 3,14 |
| 3,5 | 70 | 39 | 10 | 804.035.10 | 3661589054593 | 23,46 |
| 4 | 75 | 43 | 1 | 804.040.01 | 3661589011930 | 3,48 |
| 4 | 75 | 43 | 10 | 804.040.10 | 3661589054609 | 26,76 |
| 4,2 | 75 | 43 | 1 | 804.042.01 | 3661589011947 | 3,60 |
| 4,2 | 75 | 43 | 10 | 804.042.10 | 3661589054616 | 26,76 |
| 4,5 | 80 | 47 | 1 | 804.045.01 | 3661589011954 | 3,60 |
| 4,5 | 80 | 47 | 10 | 804.045.10 | 3661589054623 | 26,76 |
| 5 | 86 | 52 | 1 | 804.050.01 | 3661589011961 | 4,28 |
| 5 | 86 | 52 | 10 | 804.050.10 | 3661589054647 | 32,02 |
| 5,5 | 93 | 57 | 1 | 804.055.01 | 3661589011978 | 4,58 |
| 6 | 93 | 57 | 1 | 804.060.01 | 3661589011985 | 5,22 |
| 6 | 93 | 57 | 10 | 804.060.10 | 3661589054630 | 38,74 |
| 6,5 | 101 | 63 | 1 | 804.065.01 | 3661589011992 | 5,62 |
| 7 | 109 | 69 | 1 | 804.070.01 | 3661589012005 | 7,00 |
| 7 | 109 | 69 | 10 | 804.070.10 | 3661589054654 | 52,58 |
| 7,5 | 109 | 69 | 1 | 804.075.01 | 3661589012012 | 7,76 |
| 8 | 117 | 75 | 1 | 804.080.01 | 3661589012029 | 9,22 |
| 8 | 117 | 75 | 5 | 804.080.05 | 3661589054678 | 34,40 |
| 8,5 | 117 | 75 | 1 | 804.085.01 | 3661589012036 | 9,86 |
| 9 | 125 | 81 | 1 | 804.090.01 | 3661589012043 | 12,40 |
| 9 | 125 | 81 | 5 | 804.090.05 | 3661589054685 | 46,38 |
| 9,5 | 125 | 81 | 1 | 804.095.01 | 3661589012050 | 12,62 |
| 10 | 133 | 87 | 1 | 804.100.01 | 3661589012067 | 13,66 |
| 10 | 133 | 87 | 5 | 804.100.05 | 3661589054692 | 51,12 |
| 11 | 142 | 94 | 1 | 804.110.01 | 3661589012081 | 16,98 |
| 12 | 151 | 101 | 1 | 804.120.01 | 3661589012104 | 20,10 |
| 13 | 151 | 101 | 1 | 804.130.01 | 3661589012128 | 25,48 |

HSS
CO5

DIN338