WOODWORKING MACHINERY



PON250 (SINGLE-PHASE)

DISC & BELT SANDER WITH STAND • 250 MM





- Cast iron body combining strength and stability, with fixing holes on the base.
- Sawdust collector on the belt, Ø 62mm suction outlet in common with the disc which facilitates the connection with a vacuum.
- Limiting plate at the end of the sanding belt table, it also can be used as a workpiece support when the sanding belt table is raised at 90 °.
- Quick release belt tension lever located at the front of the machine, while the belt tracking knob is located at the back.





Mitre guide

Belt adjustable from 0° to 90°



Cast iron table tilting at 45°

WARRANTY	2
Motor power (230 V - 50 Hz)	800 W - S1
Dimensions	630 x 540 x 470 mm
Table dimensions	355 x 200 mm
Tilt	downward 45°
Angle guide	- 60° to + 60°
Suction outlet	ø 62 mm
Sanding disc	
Diameter	250 mm
Attachment	adhesive
Rotation speed	1400 rpm
Sanding belt	
Belt dimensions	1219 x 150 mm
Speed	517 m/min
Tilt	0° and 90°
Work table length	500 mm
Net weight	54 Kg
Spare parts reference	190100 (+ N°/ exploded view)
Gencod	3700501700276
Packing	
- Machine	720 x 410 x 440 mm
- Stand	770 x 80 x 150 mm
Gross weight	56 Kg
	

ACCESSORIES AND OPTIONS

•The machine comes with a 4-leg stand, mitre guide, 1 self-adhesive Grit 80 disc, 1 Grit 80 belt, spanners and instructions manual.



