



**PRE020 (SINGLE-PHASE)**  
**BENCH DRILL PRESS • 20 MM**  
**PRC020 (SINGLE-PHASE)**  
**FLOOR DRILL PRESS • 20 MM**



- Table, base and drilling head in cast iron.
- Base drilled to be fixed on a workbench (PRE020) or on the floor (PRC020).
- Spindle mounted on ball bearings.
- Wet table rotating at 360 ° and tilting up to 45 °.
- Rack & pinion table raising and lowering system.
- Adjustable depth stop for accurate and repetitive drilling operations.
- Capstan arms fitted with « Softgrip » handles.
- 100 mm (4") vice.
- Keyless chuck B18.



Emergency stop push-button



Steel pulleys



Adjustable chuck guard

	PRE020	PRC020
<b>WARRANTY</b>	2	2
<b>Motor power (230 V - 50 Hz)</b>	600 W - S1	600 W - S1
<b>Motor rotation speed</b>	1400 rpm	1400 rpm
<b>Dimensions</b>	690 x 350 x 1060 mm	690 x 350 x 1630 mm
<b>Drilling capacity</b>	20 mm	20 mm
<b>Spindle taper</b>	CM2	CM2
<b>Column diameter</b>	73 mm	73 mm
<b>Spindle stroke</b>	80 mm	80 mm
<b>Number of speeds</b>	12	12
<b>Speed range</b>	180 - 2740 rpm	180 - 2740 rpm
<b>Throat depth</b>	190 mm	190 mm
<b>Table/spindle distance</b>	470 mm	700 mm
<b>Base/spindle distance</b>	600 mm	1190 mm
<b>Collar diameter</b>	47 mm	47 mm
<b>Table dimensions</b>	305 x 305 mm	305 x 305 mm
<b>Base dimensions</b>	485 x 290 mm	485 x 290 mm
<b>Net weight</b>	55 Kg	61 Kg
<b>Spare parts reference</b>	830300 (+ N°/ exploded view)	830200 (+ N°/ exploded view)
<b>Gencod</b>	3661589071651	3661589071668
<b>Packing</b>	800 x 500 x 300 mm	1410 x 490 x 235 mm
<b>Gross weight</b>	58 Kg	64 Kg

## ACCESSORIES AND OPTIONS

• The machine comes with an arbor CM2/B18, 1 keyless chuck B18, 1 drift key, 1 x 100 mm jaws vice, spanners and instructions manual.



ABR701

ABR704



ABR702

ABR705

### REF

Arbor CM2/B18	ABR701
Keyless chuck B18 1-16 mm	ABR702
Drift key	ABR704
Vice with 100 mm jaws	ABR705



**INTERAXIS**  
135 mm

