


RAD260 (SINGLE-PHASE)

PLANER/THICKNESSER WITH STAND • 260 MM




- Strong and lightweight machine with die-cast aluminum body.
- Die-cast aluminum planing tables fully rectified, with anti-noise lips, and a total length of 1035 mm.
- Planer's fence in aluminum extrusion, tiltable up to 45 °, rigid and comfortably sized.
- Reversible chips collector used in planing and thicknessing mode, with
- Ø 100 mm suction outlet: the chips collector must be well positioned in order to actuate the safety switches.



Cast iron thickening table mounted on 4 threaded rods



Driving rollers for workpiece feeding



Safety switch

WARRANTY	2
Motor power (230 V - 50 Hz)	2000 W - S1
Dimensions	1100 x 600 x 950 mm
Cutterblock rotation speed	6500 rpm
Cutterblock diameter	63 mm
Number of blades	2
Blade dimensions (mm)	260 x 18 x 1,2
Suction outlet	ø 100 mm
Planer	
Planing width	260 mm
Dimensions of tables	1035 x 280 mm
Guide dimensions	610 x 110 mm
Guide tilt	from 90° to 135°
Cutting depth	from 0 to 3,0 mm
Working height	850 mm
Thicknesser	
Thicknessing width	255 mm
Thicknessing height	160 mm
Cutting depth	up to 3 mm
Feed speed	5 m/min
Table dimensions	400 x 260 mm
Net weight	66 Kg
Spare parts reference	210000 (+ N°/ exploded view)
Gencod	3700501700290
Packing	710 x 570 x 560 mm
Gross weight	72 Kg

ACCESSORIES AND OPTIONS

- The machine comes with a 4-leg stand, tilting finishing guide, 2 reversible steel blades, 1 blade adjustment gauge, spanners and instructions manual.



REF

Mobile wheel kit 210001



260 18 1,2 Reversible steel blade

REF

210002

