


SRM100 (SINGLE-PHASE)
MANUAL METAL BAND SAW • 100 MM


- Lightweight and compact machine ideal for construction sites.
- Cast aluminum base with 4 adjustable rubber pads.
- Manual lowering of the bow with return spring.
- Bow swivel up to 45°.
- Length stop for repetitive cuts.
- Control handle with start trigger.
- Quick release blade tension lever, roller bearing blade guides.
- Electronic variator to adapt the cutting speed to the material.




Speed controller. Release lever

WARRANTY	2
Motor power (230 V - 50 Hz)	1500 W - S6 (10%)
HSS bi-metal blade dimensions M42	1140 x 13 x 0,65 mm
Cutting speed	20 - 70 m/min
Vice opening	105 mm
Bow's swivel	0 to 45°
Bow's rise	Manual
Bow's fall	Spring assisted
Cutting capacity max. at 90° ☐ ☐	100 mm - 100 x 105 mm
Cutting capacity max. at 45° ☐ ☐	55 mm - 55 x 60 mm
Dimensions with bow in high position	600 x 560 x 580 mm
Sound pressure	87,3 / 88,4 dB (A)
Sound power	96,2 / 97,4 dB (A)
Main handle vibration	0,971 m/s ²
Net weight	18 Kg
Spare parts reference	800400 (+ N°/ exploded view)
Gencod	3661589084828
Packing	560 x 370 x 410 mm
Gross weight	20 Kg

ACCESSORIES AND OPTIONS

- The machine comes with 1 length stop, 1 pair of spare carbon brushes, 4 adjustable rubber feet, 1 14TPI bi-metal HSS blade, spanners and instructions manual.


 LEM214 TO 217
 PAGE 166