


## SRM125 (SINGLE-PHASE) MANUAL METAL BAND SAW 125 MM



- Brushless DC motor: high efficiency, durability, low noise level, maintenance free.
- Lightweight and transportable machine, ideal for construction sites and work on site.
- Manual lowering of the bow with return spring.
- Bow swivel up to 60 °.
- Length stop for repetitive cuts.
- Electromagnetic switch, power indicator, control handle with start trigger.
- Blade tension adjustment handle, blade guides with bearings.
- Electronic variator to adapt the cutting speed to the material.



Speed controller  
Reset button  
Power on indicator



Blade tension adjustment  
handle

Voltage/Frequency	230 V / 50 Hz
Motor power	400 W - 56 (30%)
Rotation speed	2000 - 4200 rpm
Dimensions of the blade	1435 x 12.7 x 0.65 mm
Cutting speed	38 - 80 m/min
Vice opening	125 mm
Bow's swivel	0° to 60°
Bow's rise	Manual
Baw's fall	Spring assisted
Cutting capacities at 90°	<input type="checkbox"/> Ø 125 mm / 127 x 125 mm
Cutting capacities at 45°	<input type="checkbox"/> Ø 80 mm / 80 x 100 mm
Sound pressure LpA	77 dB (A) no load
Sound power LwA	90 dB (A) no load
Net weight	23 kg
Gross weight	25 kg
Dimensions	630 x 310 x 690 mm
Packing dimensions	730 x 383 x 455 mm
Spare parts reference	800500 (+ N°/ exploded view)
Gencod	3661589103642

### ACCESSORIES AND OPTIONS

- The machine comes with a length stop, an 8/12 TPI bi-metal HSS blade and instructions manual.

