





SRM150 (SINGLE-PHASE) METAL BANDSAW • 150 MM



- Cast iron frame and bow.
- Bow swivel up to 60 °.
- Electromagnetic switch, protection index IP54.
- Control handle with start trigger.
- Blade guide with bearings.
- Quick clamping vice.
- Manual lowering of the bow with bow return spring.
- Blade tension adjustable by handwheel.
- 2-point coolant lubrication with electro-pump device.
- Complete coolant circuit with fluid and chip recovery tank.
- Adjustable length stop for repetitive cuts.
- Gear transmission unit with hardened and grinded worm shaft and brone worm gear.
- Standard equipments include a high quality bi-metal bandsaw blade, a roller for feeding long workpiece, a strong base.



Quick-clamping lock



Bow adjustable from 0° to 60° to the left for square cuts.

WARRANTY		2
Motor power (230 V - 50 Hz)		550 W - S1
HSS bi-metal blade dimensions M42		1735 x 13 x 0.65 mm
Cutting speed		34 m/min
Vice opening		170 mm
Bow's swivel		0 to 60°
Bow's rise		Manual
Bow's fall		Spring assisted
Cutting capacity max. a 90°	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	150 - 150 - 150 x 140 mm
Cutting capacity max. a 45°	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	115 - 115 - 115 x 140 mm
Cutting capacity max. a 60°	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	70 - 70 - 70 x 90 mm
Working height		850 mm
Dimensions with bow in high position		1020 x 470 x 1520 mm
Dimensions with bow in low position		1020 x 470 x 1270 mm
Net weight (base included)		95 kg
Spare parts reference		1500 (+N°/ exploded view)
Packing n°1 Machine		930 x 470 x 480 mm
Packing n°2 stand		740 x 540 x 330 mm
Gencod		3661589056801
Gross weight		101 kg

ACCESSORIES AND OPTIONS

- The machine comes with one 14TPI bi-metal HSS blade, a cabinet stand, a length stop, a feeding roller, spanners and instructions manual.

