



SRU356 (SINGLE-PHASE)

BANDSAW WITH STAND AND PEDAL WHEEL KIT


• 355 MM



- Mechanically welded frame, rigid and strong.
- 45 ° tilting cast iron sawing table with upper and lower trunnions in die-cast aluminum.
- Upper and lower blade guides with 3 cheeks.
- Blade upper guide mounted on a rack and adjustable in height by a crank.
- Quick release blade tension lever.
- Cleaning brush on the drivewheel, allowing the blade to have a good grip.
- 2 cutting speeds by changing the position of the belt, depending on the material to be cut.
- Rip fence with graduation can be positioned on the left of the blade.
- ± 60 ° adjustable miter gauge, positionable either to the right or the left of the table.
- Safety switch on each door.



Balanced cast iron flywheels



Upper and lower roller blade guide



Table tilting at 45°.

WARRANTY	2
Motor power (230 V - 50 Hz)	1450 W - S1
Dimensions	850 x 770 x 1800 mm
Cutting width	345 mm
Cutting height	235 mm
Blade length	2630 mm
Blade width	6 to 20 mm
Table dimensions	548 x 400 mm
Table tilt	0 to 45°
Working height (with stand)	1040 mm
Flywheel diameter	350 mm
Cutting speed	440 or 900 m/min
Suction outlet	ø 100 mm
Net weight	100 Kg
Spare parts reference	110600 (+ N°/ exploded view)
Gencod	3700501703383
Packing	1300 x 460 x 590 mm
Gross weight	110 Kg

ACCESSORIES AND OPTIONS

- The machine comes with a 4-leg stand with mobile wheel kit, rip fence, mitre gauge, 1 x 10 mm blade, spanners and instructions manual.

CONSUMABLES

LEM39 TO LEM46 P. 142
LEM48 P. 164

