


## SST256 (SINGLE-PHASE)


### TABLE SAW WITH CARRIAGE FLUSH WITH THE BLADE • 255 MM




- Cabinet base stand, cast iron trunnion and heavy duty mechanism for the sawing unit.
- Cast iron main table with right and rear extensions in steel.
- Large sliding table with graduated fence and extendable stop to 2280 mm.
- Cleaning hatch on the upper cabinet, allowing the removal of sawdust and wooden scraps.
- Blade's height and tilt adjustment by two independent cranks.
- Suction outlet Ø 30 mm on the blade guard, connected to the main dust outlet by a flexible hose (supplied).



1320 mm sliding carriage flush with the blade.



Rip fence with micrometric adjustment



Frame reinforcement foot

<b>WARRANTY</b>	2
Motor power (230 V - 50 Hz)	2100 W - S6/40 %
Dimensions	2260 x 2070 x 1160 mm
Blade rotation speed	4060 rpm
Blade diameter	255 mm
Blade bore	30 mm
Blade tilt	0 to 45° on the right
Working height	850 mm
Max. cutting height.	80 mm
Cutting height at 45°	50 mm
Dimensions of table saw with extensions	1210 x 620 mm
Sliding carriage dimensions	1320 x 238 mm
Dimensions of sliding table	600 x 400 mm
Cutting stroke against crosscut fence	1200 mm
Max. cutting width against rip fence	610 mm
Suction outlet	100 mm
Net weight	152 Kg
Spare parts reference	070400 (+ N° exploded view)
Gencod :	3700501706254
Packing :	
- Machine	860 x 625 x 570 mm
- Carriage	1380 x 380 x 130 mm
- Carriage table	890 x 515 x 150 mm
- Table extensions	805 x 305 x 55 mm
Gross weight	165 Kg

## ACCESSORIES AND OPTIONS

- The machine comes with a rip fence, sliding carriage, panel stop, 1 x 36 teeth TCT saw blade, table extensions, push stick, spanners and instructions manual



**REF**

Mobile wheel kit 070410

CONSUMABLES

### SOLID WOOD

222.250.3024 P. 84

334.250.3048 P. 86

### DERIVED FROM WOOD

336.250.3060 P. 95

338TF.250.80 P. 97