



TAB040 (SINGLE-PHASE) WOOD LATHE • 406 MM




- Headstock, tailstock, and bed in cast iron for high stability and vibration-free running.
- Bed drilled to be fixed on a stand (optional) or on a workbench.
- Accessories and tools holder on the back of the bench.
- Tailstock with cam lock, live spur MT2 adjustable by handwheel.
- Headstock and tailstock drilled at 10 mm to remove either the headstock spur or the tailstock live center (push-out rod supplied), and to allow the use of a drill bit.
- 200 mm articulated tool rest in cast iron with cam lock.
- Optional bed extension to get a distance between centers of 1025 mm.



12-position indexing



M33 x 3.5 mm threaded drive spindle



6 spindle speeds

WARRANTY	2
Motor power (230 V - 50 Hz)	580 W - S1
Dimensions	990 x 290 x 450 mm
Bed height	190 mm
Number of speeds	6
Rotation speed	1 - 350 rpm 2 - 670 rpm 3 - 1025 rpm 4 - 1500 rpm 5 - 2225 rpm 6 - 3250 rpm
Distance between centres	406 mm
Swing over bed	305 mm
Tool rest length	200 mm
Headstock	
Headstock taper	CM2
Drive spindle	M33 x 3,5 mm
Indexing	12 positions
Tailstock	
Tailstock taper	CM2
Tail stock travel	65 mm
Tailstock drill hole	ø 10 mm
Net weight	42 Kg
Spare parts reference	150300 (+ N°/ exploded view)
Gencod	3700501706100
Packing	850 x 455 x 290 mm
Gross weight	47 Kg

ACCESSORIES AND OPTIONS

- The machine comes with 1 face plate Ø 150 mm, tool rest, 1 drive center, 1 live center, 1 knockout rod, 1 accessory holder, spanners and instructions manual.



OPTION

	REF
Bed Extension 620 mm	150303
Stand Extension	150302
Stand	150301



PAGE 427