


## TAB110 (SINGLE-PHASE) WOOD LATHE • 1100 MM



- Cast iron stand with provision for a shelf, stable and aesthetic.
- Cast iron bed drilled to be fixed on the supplied stand or on a workbench.
- Rotation speed can be changed automatically by steps, without having to touch the belt.
- 300 mm articulated tool rest in cast iron with cam lock: can be used with or without the extension arm.
- Headstock and tailstock drilled at 10 mm to remove either the headstock spur or the tailstock live center (push-out rod supplied), and to allow the use of a drill bit.



Head rotation up to 180°



CM2 M33 x 3.5 threaded drive spindle.



Headstock and tailstock drilled at 10 mm

<b>WARRANTY</b>	2
Motor power (230 V - 50 Hz)	1100 W - S1
Dimensions	1700 x 420 x 1180 mm
Bed height	890 mm
Number of speeds	10
Rotation speed (variable)	From 500 to 2000 rpm
Distance between centres	1100 mm
Swing over bed	400 mm
Tool rest length	300 mm
Headstock rotation	0° - 60° - 90° - 120° - 180°
Drive spindle	M33 x 3,5
Headstock taper	CM2
Tailstock taper	CM2
Tailstock drill hole	ø 10 mm
Net weight	130 Kg
Spare parts reference	150100 (+ N°/ exploded view)
Gencod	3700501700214
Packing	1620 x 450 x 520 mm
Gross weight	140 Kg

### ACCESSORIES AND OPTIONS

- The machine comes with a cast iron stand, tool rest, 1 face plate Ø 150 mm, 1 drive center, 1 live center, 1 knockout rod, spanners and instruction manuals.



#### REF

Adjustable Suction Nozzle	BAS100
Lathe copying device 1010 mm	COP110



#### REF

Steady rest	150100.LUN
-------------	------------

